

SPECIFICATION

TITLE

"POSITIONING DEVICE FOR AN IMAGING DIAGNOSIS SYSTEM"

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention is directed to a positioning device for an imaging diagnosis system of the type having a patient bed on which a patient can be moved from an exterior preparation position into the diagnosis system, a picture screen, and one or more cameras is arranged over and/or next to the patient bed in the region of the preparation position and coupled with the picture screen, and a computer.

Description of the Prior Art

It is essential in all diagnosis systems that the body part of the patient to be examined must be positioned in the central region of the device. Usually this ensues by manual displacement of the patient under a laser aiming device. The region to be examined is coarsely identified in on with the laser, and an automatic positioning of this location then is effected in the central region.

German OS 195 08 715 discloses attachment of a marking on the patient in the region of the desired examination region, the spatial position thereof being determined with the assistance of a video camera outside of the examination space of a diagnosis device. The position determined in this way is employed for the targeted position of the patient bed.

In scanning imaging diagnosis systems, the determination of the scan length or the scan region ensues on a separate picture screen. A screen scan of the patient is thereby usually also implemented in advance, the image planes then being entered with reference to the screens can result.

This positioning that has been conventionally undertaken is rather complicated, particularly in the case of scanning devices, and is also somewhat imprecise, as well as being relatively time-consuming, so that the overall examination time is lengthened as a result, and thus the utilization of the expensive imaging diagnosis devices remain unsatisfactory.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a positioning device for imaging diagnosis systems of the type initially described wherein a simple, fast and exact positioning of every desired body part in the center of the device can be achieved.

This object is achieved in accordance with the invention in a diagnostic imaging system wherein the desired examination region can be selected in the patient image on the picture screen with a region selection device in order to automatically move the patient with the selected examination region into the imaging diagnosis system, the patient being on a patient bed provided with a position acquisition device. The selected examination region is brought into a central region or in some other optimum region of the diagnostic imaging system.

The region selection device, for example, can be a mouse and/or a touch screen.

Particularly in a scanning, imaging diagnosis system, not only the selection of the desired examination region in view of its central position can be selected via a mouse, a touch screen or the like, but also a scan length and/or a scan region can be selected, with the exact position and size of the scan region being displayed in the picture screen over a selection frame. In conjunction with the fixed camera position and the examination region selected in the overall image of the patient on the picture screen, the computer can move the patient bed, controlled in this way, provided with a position

acquisition of the patient 3 with the camera 4. Thus a plane selection or region selection in two or three dimensions. Preferably, however, instead of the patient-monitoring camera being used for this purpose, a second camera is provided next to the patient bed. Also, a collision monitoring camera 9 is provided to prevent a body part of the patient 3 or a supply hose or the like from being shifted laterally too far from the center, so that it could strike against the imaging diagnosis system 1 when introduced thereinto.

A component of the computer 6 is a memory 11 in which image data of the patient image and position data with respect to the desired examination region 13 can be stored, so that another region selection, i.e. a renewed positioning, is possible by reading out that data without the patient 3 having to be moved out of the diagnosis device for defining the region, which can be a different region.

Although modifications and changes may be suggested by those skilled in the art, it is in the intention of the inventors to embody within the patent warranted hereon all changes and modifications as reasonably and properly come within the scope of their contribution to the art.